

CODE : FLM0092 DATE: 04/11/2022


PPTCGLOSSWHITECAV60/RF20/WG62

PRODUCT
DESCRIPTION /
BENEFITS

Face: Gloss white top coated cavitated polypropylene.

Adhesive: Removable acrylic water based adhesive. Good long-term removability from a wide variety of surfaces.

Liner: White supercalendered glassine paper. There may be slight variations in tone.



TYPICAL USE	Health & Personal Care
PRINTING & CONVERTING	Suitable for printing in Flexography, Offset, Screen, hot-foil and Thermal Transfer. Testing for suitability between media, printers and inks is always recommended prior to use.
PRODUCT RECOMMENDATIONS	Multipurpose removable labels for industrial use. Not recommended for fan-folding applications. Prolonged exposure to UV light may adversely affect clean removability. Product must be tested thoroughly before approval.
SHELF LIFE	2 years, under storage conditions as defined by FINAT section 2.5 (20-25°C, 40-50% RH). Prolonged storage at

2 years, under storage conditions as defined by FINAT section 2.5 (20-25°C, 40-50% RH). Prolonged storage at higher temperatures and/or humidity levels will shorten the shelf life of the product.



CODE: FLM0092 DATE: 04/11/2022

PPTCGLOSSWHITECAV60/RF20/WG62

PHYSICAL PROPERTIES / TYPICAL VALUES

FACE MATERIAL		
PP TC GLOSS WHITE CAV 60		
Grammage	40 Gr/m2	ISO 536
Thickness	57 µm	ISO 534-80
Finishing	Gloss White	

ADHESIVE			
RF20			
Tack (N) Glass	3 N/mm	FTM9	
Min Labelling temperature	0℃		
Usage Temperature	-5/+60°C		

LINER		
WG62		
Grammage	58 Gr/m2	ISO 536
Thickness	51 µm	ISO 534-80

QUALITY CERTIFICATIONS • Suitable for direct food contact with dry, moist and non-fatty food. More information on equest.

DISCLAIMER

Information on physico-chemical characteristics and values in this document are based upon tests we believe to be reliable and do not constitute a warranty. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material to their specific use. All technical data are subject to change. All Fedrigoni products are sold subject to terms and conditions of sale. For more information, contact your Fedrigoni sales representative. In case of any ambiguities or differences between the English and foreign versions of this document, the English version shall be prevailing and leading.