



## Product Data Sheet # MLF25TT

### Self Wound Polypropylene Overlaminating Film

Face Stock	-----	Matt polypropylene Biaxially Oriented
Adhesive	-----	Water-based Acrylic
Adhesion/Stainless Steel	-----	15 oz./inch width
Service Temperature	-----	32° to 150° F / 0° to 70°C
Tensile	-----	19 lb./inch width
Elongation	-----	190 %
Film Thickness	-----	1,0 mil (25 micron)
Overall Thickness	-----	1.5 mil (37.5 micron)
UV Resistance	-----	Good
FDA Approved	-----	21 CFR 175.105 21 CFR 177.10520
Outdoor Weathering	-----	Fair to Good

- This product is a matt transparent, pressure sensitive tape that can be used as an **overlamine** to enhance, protect, and extend the life of printed labels.
- Serves as a **reinforcement, surface protector, and tape seal** due to its ability to adhere to hot and cold periods.
- Resistant to **moisture, chemicals, thinners, oils, and acids.**

Version June 2020

IMPORTANT NOTICE TO BUYER: All statements, information, and recommendations contained herein are based on calculation and tests we believe to be reliable. Accuracy or compliances thereof is not guaranteed. Before using, user shall determine suitability of the tape for its intended use and user assumes all risk and liability whatsoever in connection therewith. Seller neither makes, nor shall not be bound by, and warranty, express, implied, statutory or otherwise. The seller limits its obligation to replacement or, at its option, reimbursement of the purchase price of tape shown to the seller's satisfaction to have been defective at the time the seller sold it.